



ANE-BD19HD10-O

1.0 Megapixel 720P AHD Camera

Features

- 1/4" 1.0 Megapixel Colour CMOS (OV9712)
- Resolution: 1280(H) × 720(V) 1.0 Mega Pixels
- Min. illumination: 0Lux/F1.2 (IR ON)
- UP to 20 meters IR Distance
- IR cut function, Day @ Night surveillance
- Non coding compression, High efficiency, without delay real-time transmission
- Up to 500 meters lossless transmission with 75-3 coax
- Compatible with normal D1/960H
- Support 2D noise reduction, Lightning protection, anti-fog function
- Metal housing, Inner line bracket, multiple angle adjustable
- Waterproof Level: IP66





Technical Specifications

Model	ANE-BD19HD10-O
Camera	
Image Sensor	1/4" 1.0Megapixel pixel Colour CMOS(OV9712)
Resolution	AHD 720P / CVBS 800 TVL
Effective Pixels	1280(H)×720(V) 1.0M Pixels
Electronic Shutter	PAL:1/50 ~ 1/100,000s NTSC:1/60 ~ 1/100,000s
System	PAL/NTSC
Min. Illumination	Color:1.0Lux(F1.2,50IRE,AGC ON),Black and White:0.1Lux(F1.2,50IRE,AGC ON)
Video Output	1.0Vp-p composite output, 75Ω
Camera Features	
Max. IR LED Distance	15~20m, 24pcs Φ5/850nm IR LED
Day/Night	ICR switch
S/N Ratio	≥60dB(AGC Off)
White Balance	Auto
WDR	Digital WDR
Frame accumulation	0-30X
2D-DNR	Off/Low/Middle/High
Image Freeze	Support
BLC/HLC	Support



Anti-fog	0-2 grade
Mirroring	Horizontal mirror/vertical mirror
Privacy Mask	Support
Lens	
Focal length	3.6/6mm Fixed lens (M12)
General	
Power Supply	DC12V±10%
Power Consumption	0.72W/2.64W(IR ON)
Working Environment	-20°C~+60°C
Transmission Distance	Over 500m via 75-3 coaxial cable
Size	172x65x62mm
Weight	0.48KG
Language	Chinese / English / German / French / Italian / Spanish / Portuguese / Russian / Dutch / Turkish / Poland
Humidity	Relative humidity below 90%



Dimensions (mm)

