



ANE-DM19HD10-O

1.0Mp 720P AHD Dome Camera 3.6mm Fixed Lens

Features

- > 1/4" 1.0 Megapixel Colour CMOS
- > Resolution: 1280 (H) x 720 (V) 1.0MP
- > Min Illumination 0Lux / F1.2 (IR on)
- > Up to 30 meters IR Distance
- > IR cut function / Day & Night surveillance
- > Non coding compression, High efficiency, without delay, real time transmission
- > Up to 500m lossless transmission with 75-3 Coaxial cable
- > Compatible with normal D1 / 960H
- > 3.6mm fixed lens
- > Support 2D noise reduction, Lightning protection, Anti-fog function
- > Metal housing, inner line bracket, multiple angle adjustable
- > IP66 – Waterproof level





Technical Specifications

Model	ANE-DM19HD10-O
General	
Operating System	Embedded LINUX
Resource	Simultaneous remote monitoring, local recording and remote control
Transmission Distance	Over 500m via 75-3 Coaxial cable
System	PAL / NTSC
Image Resolution	AHD 720P / CVBS 800 TVL
User Interface	WEB, CMS, NVR
Camera	
Image Sensor	1/4" 1.0 Megapixel Colour CMOS
Max IR LED Distance	25-39m 36pcs 5/850nm IR LED
Effective Pixels	1280 (H) × 720 (V) 1.0 Mp
Electronic Shutter	PAL 1/50 to 1/000000s NTSC 1/60 to 1/100000s
Mini. Illumination	Colour: 0.1 Lux (F1.250 IREAGC ON) Black and White :0.1Lux (F1.250 IREAGC ON)
Day / Night	IRC switch
Signal Noise Ratio	>60dB (AGC Off)
White Balance	Auto
WDR	Digital WDR
Frame Accumulation	0-30X
2D-DNR	Off / low / middle / high
Image Freeze	Support



BLC / HLC	Support
Anti-fog	0-2 Grade
Lens	
Focal Length	3.6mm fixed lens
Environmental	
Power Supply	DC12V (10%)
Power Consumption	<0.72W / 3.6 W (IR on)
Dimensions(mm)	119mm × 98mm
Weight(kg)	0.85Kg
Working Environment	-20°C ~ + 60°C
Language	Chinese / English / German / French / Italian / Spanish / Portuguese / Russian / Dutch / Turkish / Polish
Humidity	Relative humidity below 90%



Dimensions (mm)

